



Dimensioni Flange - Dimensions Flange EN1092-1/2 PN10					
DNa-DNm	65	80	100	125	150
CF	145	160	180	210	240
CE	185	200	220	250	285
iF	18	18	18	18	22
zF	4	8	8	8	8

ACCOPIAMENTO POTENZA - POLARITÀ / GRANDEZZA MOTORE POWER - POLARITY / MOTOR SIZE COUPLING															
2POLI	GRAND.	71	80	80	90S	90L	100L	112M	132S	132S	132M	160M	160M	160L	180M
	kW	0,55	0,75	1,1	1,5	2,2	3	4	5,5	7,5	9,2	11	15	18,5	22
4POLI	GRAND.	80	80	90S	90L	100L	100L	112M	132S	132M	132M	160M	160L	180M	180L
	kW	0,55	0,75	1,1	1,5	2,2	3	4	5,5	7,5	9,2	11	15	18,5	22
6POLI	GRAND.	80	90S	90L	100L	112M	132S	132M	132M	160M	160L	180L	-	-	-
	kW	0,55	0,75	1,1	1,5	2,2	3	4	5,5	7,5	11	15	-	-	-

Pompa tipo Pump size	Grandezza motore Motor size	DIMENSIONI - DIMENSIONS [mm]																				Peso weight ^(a) [kg]
		DNa	DNm	a	f	h1	h2	b	m1	m2	n1	n2	n3	w	s1	s2	c	c1	l1	l2	T ^(a)	
65-20	100	80	65	66	269	180	225	65	125	95	320	250	110	222	14	15	16	0	151	151	724	97
	112	80	65	66	269	180	225	65	125	95	320	250	110	222	14	15	16	0	151	151	728	104
	132	80	65	66	289	180	225	65	125	95	320	250	190	249	14	15	16	0	151	151	857	130
	160	80	65	66	319	180	225	65	125	95	320	250	212	267	14	19	16	0	151	151	1040	222
	180	80	65	66	319	180	225	65	125	95	320	250	212	267	14	19	16	0	151	151	1094	287
80-20	100	100	80	68	277	180	250	65	125	95	345	280	110	230	14	15	16	0	159	159	734	101
	112	100	80	68	277	180	250	65	125	95	345	280	110	230	14	15	16	0	159	159	738	108
	132	100	80	68	297	180	250	65	125	95	345	280	190	257	14	15	16	0	159	159	867	134
	160	100	80	68	327	180	250	65	125	95	345	280	212	275	14	19	16	0	159	159	1050	226
	180	100	80	68	327	180	250	65	125	95	345	280	212	275	14	19	16	0	159	159	1104	291
80-25	100	100	80	75	282	225	280	70	160	120	395	315	110	235	18	15	18	0	176	176	746	121
	112	100	80	75	282	225	280	70	160	120	395	315	110	235	18	15	18	0	176	176	750	128
	132	100	80	75	302	225	280	70	160	120	395	315	190	262	18	15	18	0	176	176	879	154
	160	100	80	75	332	225	280	70	160	120	395	315	212	280	18	19	18	0	176	176	1062	246
	180	100	80	75	332	225	280	70	160	120	395	315	212	280	18	19	18	0	176	176	1116	311
100-25	112	125	100	90	292	225	280	80	160	120	400	315	110	245	18	15	18	0	183	216	775	146
	132	125	100	90	312	225	280	80	160	120	400	315	190	272	18	15	18	0	183	216	904	172
	160	125	100	90	342	225	280	80	160	120	400	315	212	290	18	19	18	0	183	216	1087	263
	180	125	100	90	342	225	280	80	160	120	400	315	212	290	18	19	18	0	183	216	1141	328
125-25	112	150	125	112	304	250	355	80	160	120	400	315	110	258	18	15	18	0	208	254	809	170
	132	150	125	112	324	250	355	80	160	120	400	315	190	285	18	15	18	0	208	254	938	196
	160	150	125	112	354	250	355	80	160	120	400	315	212	303	18	19	18	0	208	254	1121	288
	180	150	125	112	354	250	355	80	160	120	400	315	212	303	18	19	18	0	208	254	1175	353